

SmartSense Sensor Hub

External Sensor Support for BZ Gateways

The SmartSense Sensor Hub is an accessory that connects with the SmartSense BZ Gateway to enable the use of external sensors (i.e. O₂, CO₂, differential pressure, etc.) and PoE (Power Over Ethernet). Sensor Hub easily connects with existing BZ Gateways.

Features

- Enables support for external sensors such as O₂, CO₂, differential pressure, and more.
- Easy setup via the SmartSense Install app.
- Easily connects to the BZ Gateway.



Specifications

Product SKU	TM-SENSORHUB
Dimensions	5.7" x 3.6" x 1.7" (145.3mm x 90.8mm x 43.7mm)
Weight	4.3oz (122.2g)
Network Requirements	10/100 Ethernet option
Device Operating Range	5°C to 35°C (40°F to 95°F)
Power Source	100VAC-240VAC, 50Hz/60Hz or PoE IEEE 802.3af
Sensor Type	4-20mA, 24VDC
24VDC Source	100mA max
Maximum Sensors	4 Sensors
Storage Temperature	Short-term and long-term: -20°C to 45°C (-4°F to 113°F)
LED Activity	LED status indicator on device

For more information about SmartSense Sensor Hub visit www.smartsense.co or call +1 (866) 806-2653